

B51V63 Commercial Duty



3 HP
11.5 cfm @ 175 psi

5 HP
16 cfm @ 175 psit

Features

- ASME/CRN 200 psi MWP air receiver
- Auto start stop
- Bearings on both end of the crank shaft
- Cast iron two-stage compressor pump
- Disk & spring valves
- Heavy duty air filter
- Motor overload protection built-in
- Needle bearings and inserts on compression rod
- Stainless steel flexible discharge line
- Swedish steel valve components
- UL/CSA electric control components

Options

- Automatic tank drain
- Belt guard cooler
- NEMA7
- TEFC
- 3-phase drive motor & controls



Picture representative
of 60/80 gallon tank mount

Model	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt
B31V63	1	208-230	60 Gallon Vertical	30	25	74	18
B31V83	1	208-230	80 Gallon Vertical	30	25	74	18
B51V63	1	208-230	60 Gallon Vertical	30	25	74	22
B51V83	1	208-230	80 Gallon Vertical	32	26	74	22

No Start Up Kit Required

Optional 5-year Pump Warranty Available

See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 7-2019

