7.5 HP Duplex







Basic Compressor Features

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two-stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-groove B width motor pulley
- 2-piece tank top plate design

Elite Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada

48 cfm @ 175 psi (Time Delay)

24 cfm @ 175 psi (Alternating)



Air cooled after cooler on Elite unit



Model	Phase	Voltage	Tank	Length	Width	Height
DB71H124	1	208-230	120 Gallons	86	30	50
DB73H124	3	208-230/460	120 Gallons	86	30	50
Add -E to model number to make Elite Unit						

No Start Up Kit Required

Optional 5-year Pump Warranty Available

See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.



