

25 HP Duplex Rotary Screw



204 cfm @ 150 psi

216 cfm @ 125 psi

Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- ASME Powder coated air receiver
- Automatic tank drain
- Baldor electric motors
- Easy to read and access gauges
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy-duty air filter
- IEC contactors
- Omega profile rotors
- Single control solenoid operation
- Spin on oil filter
- Spin on separator
- SMART contact controls
- Stainless steel discharge lines
- Timed shutdown
- UL control components
- Vibration isolation pads



| Model Number | Phase | Voltage | Tank | Length | Width | Height | Amp Draw 230 Volt | Amp Draw 480 Volt |
|--------------|-------|-----------------|-----------------------|--------|-------|--------|-------------------|-------------------|
| DRS253H120-E | 3 | 208-230/460-480 | 120 Gallon Horizontal | 78 | 56 | 62 | 63 | 31 |

No Start Up Kit Required

Optional 5-year Pump Warranty Available

See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 3-2019

