

40 HP Rotary Screw



160 cfm @ 125 psi

155 cfm @ 150 psi

Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- ASME Powder coated air receiver
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy-duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin-on oil filter
- Spin-on separator
- TEFC drive motor (3 phase only)
- UL control components

Elite Stainless Features

- All Elite features
- First oil and filter change
- Stainless steel discharge lines
- Stainless steel 12 inch install line
- Tank discharge ball valve

Elite Compressor Features

- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Tank discharge ball valve
- Freight pre-paid in the 48 states & southern Canada



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
RS403H120	3	208-230-460	120 Gallon Horizontal	72	38	54	92	46

Add -E after part number to make Elite Model

No Start Up Kit Required

Optional 5-year Pump Warranty Available

See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 3-2019

