

# 20 HP Reciprocating



**78 cfm @ 175 psi**

## Basic Compressor Features

- Access to compressor valves without compressor head removal
- All UL electrical controls
- ASME tested powder coated steel tank
- Auto start stop
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Disk and spring valves
- Fully enclosed belt guard
- Heavy-duty air filter
- Heavy-duty two stage solid cast iron pump
- Industrial grade electric motor
- Magnetic starter mounted and wired
- Needle bearings, and inserts on rods
- Stainless steel flex air lines
- Swedish steel valves
- TEFC drive motor (3 phase only)
- Torrington needle bearings
- 2-grove B width motor pulley
- 2-piece tank top plate design

## Elite Compressor Features

- All basic features
- Automatic tank drain
- Belt guard after cooler
- Low oil monitor
- Tank discharge ball valve
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Air cooled after cooler on Elite unit



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
<b>B203H129</b>	3	208-230-460	120 Gallon Horizontal	70	38	60	54	27
<b>B203H249</b>	3	208-230-460	240 Gallon Horizontal	85	46	72	54	27

Add -E after part number to make Elite Model

**No Start Up Kit Required**

**Optional 5-year Pump Warranty Available**

See catalog for additional options

## Compressed Air Systems

**Simplicity. It's What We Do.**

**compressed-air-systems.com** | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 3-2019

