

3-5 HP LDV95 Reciprocating



3 hp 11.5 cfm @ 175 psi
5 hp 11.5 cfm @ 175 psi

Features

- Cast iron two stage compressor pump
- Bearings on both end of the crank shaft
- Needle bearings and inserts on compression rod
- ASME/CRN 200PSI MWP Air receiver
- UL/CSA electric control components
- Auto start stop
- Heavy duty air filter
- Swedish steel valves

Options

- 3 Phase drive motor & controls
- TEFC
- NEMA7
- Automatic tank drain
- Belt guard cooler



Picture representative of 60 gallon tank mount



Picture representative of 80 gallon tank mount

Model	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt
B31V63	1	208-230	60 Gallon Vertical	30	25	74	18
B31V83	1	208-230	60 Gallon Vertical	30	25	74	18
B51V63	1	208-230	60 Gallon Vertical	30	25	74	22
B51V83	1	208-230	60 Gallon Vertical	32	26	74	22

No Start Up Kit Required

Optional 5-year Pump Warranty Available. See catalog for additional options.

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 4-2017

