

25 HP Duplex



**184 cfm @ 175 psi
(Time Delay)
92 cfm @ 175 psi
(Alternating)**

Basic Compressor Features

- Heavy Duty two stage solid cast iron pump
- Disk and spring valves
- Bearings on both ends of the crank shaft
- Needle bearings, and inserts on rods
- Industrial grade electric motor
- ASME tested powder coated steel tank
- 2 grove B width motor pulley
- All UL electrical controls
- Access to compressor valves without compressor head removal
- Auto start stop
- Fully enclosed belt guard
- Centrifugal unloader
- Heavy duty air filter
- Swedish steel valves
- Torrington needle bearings
- Control panel mounted and wired

Elite Compressor Features

- All basic features
- Low oil monitor
- Automatic tank drain
- Vibration pads
- Tank discharge ball valve
- Freight pre-paid in the 48 states & southern Canada



Air cooled after cooler Elite unit



Model	Voltage	Tank	Elite/Basic	Length	Width	Height
DB253H249	208-230/460-480	240 Gallon	Basic	85	52	72
Add -E to model number to make Elite Unit						

No Start Up Kit Required

Optional 5-year Pump Warranty Available. See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 7-2016

