

# 70 DBA 7.5 HP Duplex Enclosed Rotary Screw



52 cfm @ 150 psi

58 cfm @ 125 psi

## Features

- Air/oil cooler
- German manufactured airend
- SMART contact controls
- Timed Shutdown
- Automatic tank drain
- Vibration isolation pads
- IEC Contactors
- UL electrical components
- Spin on separator
- Heavy duty air filter
- ASME certified Tank
- Baldor electric motors
- Powder coated tank
- Factory filled with fully synthetic fluid
- Omega Profile rotors
- Single solenoid operation
- Stainless steel discharge lines
- Sound dampening enclosure
- Grass hopper style tank



Model	Voltage	Amp Draw	Tank	Length	Width	Height
DRS73ENC-CRD	208-230/460-480	230 Volt-36 480 Volt-18	120 Gallon	98	36	78
DRS71ENC-CRD	208-230	230 Volt-64	120 Gallon	98	36	78

No Start Up Kit Required

Optional 5-year Pump Warranty Available. See catalog for additional options

## Compressed Air Systems

Simplicity. It's What We Do.

[compressed-air-systems.com](http://compressed-air-systems.com) | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 8-2018

