

15 HP Enclosed Rotary Screw



55 cfm @ 150 psi
68 cfm @ 125 psi
73 dba

Features

- Airend manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL control components
- Automatic belt tensioning
- Omega profile rotors
- Air/oil cooler
- Heavy duty air filter
- Easy to access oil cooler for cleaning
- Operating pressures from 100-190 psi available
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- Solid steel sound enclosure
- Vertical draft ventilation

CRD Compressor

Features

- All basic features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- ASME powder coated air receiver
- Refrigerated air dryer
- Stainless Steel discharge lines
- Free freight in the 48 states & southern Canada



| Model Number | Phase | Voltage | Tank | Package | Length | Width | Height | Amp Draw 230 Volt | Amp Draw 480 Volt |
|--------------|-------|-------------|----------------------|---------|--------|-------|--------|-------------------|-------------------|
| RS153ENC | 3 | 208-230-460 | 80 Gallon Horizontal | Basic | 41 | 36 | 46 | 42 | 21 |
| RS153ENC-CRD | 3 | 208-230-460 | 80 Gallon Horizontal | CRD | 64 | 37 | 68 | 42 | 21 |

No Start Up Kit Required

Optional 5-year Pump Warranty Available. See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 4-2017

