

7.5 HP Enclosed Rotary Screw



26 cfm @ 150 psi
29 cfm @ 125 psi
70 dba

Features

- Airend manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL control components
- Automatic belt tensioning
- Omega profile rotors
- Air/oil cooler
- Heavy duty air filter
- Easy to access oil cooler for cleaning
- Operating pressures from 100-190 psi available
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- Solid steel sound enclosure
- Vertical draft ventilation

CRD Compressor

Features

- All basic features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- ASME powder coated air receiver
- Refrigerated air dryer
- Stainless Steel discharge lines
- Free freight in the 48 states & southern Canada



Model Number	Phase	Voltage	Tank	Package	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
RS71ENC	1	208-230	80 Gallon Horizontal	Basic	32	28	42	32	N/A
RS71ENC-CRD	1	208-230	80 Gallon Horizontal	CRD	64	28	63	32	N/A
RS73ENC	3	208-230-460	80 Gallon Horizontal	Basic	32	28	42	18	9
RS73ENC-CRD	3	208-230-460	80 Gallon Horizontal	CRD	64	28	63	18	9

No Start Up Kit Required

Optional 5-year Pump Warranty Available. See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 4-2017

