

39 CFM Gas/Diesel Rotary Screw

39 CFM @ 150 PSI

Basic Compressor

Features

- Airend manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Single control solenoid operation
- UL control components
- Easy to remove bolt on oil cooler for cleaning
- Operating pressures from 100-190 PSI available
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- Industrial Duty Drive engine

Elite Compressor

Features

- All basic features
- Air/Oil cooler
- SIMPLEX controls
- Vibration isolation pads
- Battery mounted and wired
- Free freight in the 48 states & southern Canada

Elite Stainless

Features

- All Elite features
- Stainless Steel discharge lines
- Tank discharge ball valve
- Stainless Steel 12 inch install line
- First oil and filter change



Model	HP	Mount	Tank	Elite/Basic	Drive engine	Length	Width	Height
RS180GED30	17	Tank mount	30 Gallon Horizontal	Basic	Kohler Diesel	48	30	48
RS180GED30-E	17	Tank mount	30 Gallon Horizontal	Elite	Kohler Diesel	48	30	48
RS180GEH30	18	Tank mount	30 Gallon Horizontal	Basic	Honda	48	30	48
RS180GEH30-E	18	Tank mount	30 Gallon Horizontal	Elite	Honda	48	30	48
RS180GEC30	18	Tank mount	30 Gallon Horizontal	Basic	Kohler	48	30	48
RS180GEC30-E	18	Tank mount	30 Gallon Horizontal	Elite	Kohler	48	30	48

*Unit does not come standard with a fuel tank

No Start Up Kit Required

See catalog for additional options.



Compressed Air Systems

Simplicity. It's What We Do.

www.compressed-air-systems.com

