

100 HP Open Rotary Screw



Basic Compressor Features

- Aired manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL control components
- Omega profile rotors
- Air/oil cooler
- Easy to remove bolt on oil cooler for cleaning
- Operating pressures from 100-190 psi available
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- ASME Powder coated air receiver
- Heavy duty air filter

Elite Stainless Features

- All Elite features
- Stainless steel discharge lines
- Tank discharge ball valve
- Stainless steel 12 inch install line
- First oil and filter change

450 cfm @ 120 psi

400 cfm @ 150 psi

Elite Compressor Features

- All basic features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Freight pre-paid in the 48 states & southern Canada



Model Number	Phase	Voltage	Tank	Elite/Basic	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
RS1003BM	3	208-230-460	N/A	Basic	84	60	48	238	119
RS1003BM-E	3	208-230-460	N/A	Elite	84	60	48	238	119

No Start Up Kit Required

Optional 5-year Pump Warranty Available. See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 4-2017

