

75 HP Open Rotary Screw



Basic Compressor Features

- Aired manufactured with German rotary screw components
- Spin on separator
- Spin on oil filter
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- UL Control components
- Omega profile rotors
- Air/Oil cooler
- Easy to remove bolt on oil cooler for cleaning
- Operating pressures from 100-190 PSI available
- Extended oil drain with ball valve for easy service
- Easy to read and access gauges
- Factory filled with premium synthetic fluid
- ASME Powder coated air receiver
- Heavy duty air filter

Elite Compressor Features

- All basic features
- Automatic tank drain
- SMART contact controls
- Vibration isolation pads
- Freight pre-paid in the 48 states & southern Canada

Elite Stainless Features

- All Elite features
- Stainless Steel discharge lines
- Tank discharge ball valve
- Stainless Steel 12 inch install line
- First oil and filter change

325 cfm @ 125 psi

285 cfm @ 150 psi



Model Number	Phase	Voltage	Tank	Elite/Basic	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
RS753H120-E	3	208-230-460	120 Horizontal	Elite	80	48	78	172	86
RS753BM-E-EVO	3	208-230-460	Base mount	Elite	80	48	56	172	86
RS753H120	3	208-230-460	120 Horizontal	Basic	80	48	78	172	86
RS753BM-EVO	3	208-230-460	Base mount	Basic	80	48	56	172	86

No Start Up Kit Required

See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 7-2016

