

# 7.5 HP G Series Open Rotary Screw



25 cfm @ 150 psi

## Basic Compressor Features

- Spin on separator
- Spin on oil filter
- Simplified operating controls  
(No complicated micro-processor)
- Single control solenoid operation
- UL control components
- Alpha profile rotors
- Air/oil cooler
- Easy to remove bolt on oil cooler
- Standard operating pressure 175 psi
- Extended oil drain for easy service
- Factory filled with premium synthetic fluid
- ASME/CRN powder coated receiver
- Heavy duty air filter
- Automatic tank drain
- Smart contractor
- Vibration isolation pads
- Tank discharge ball valve
- TEFC drive motor (3 phase only)
- Free freight in CAS freight pre-paid area & southern Canada



Model Number	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
RS71V80-GCU	1	208-230	80 Gallon Vert	25	25	78	31	N/A
RS73V80-GCU	3	208-230/460-480	80 Gallon Vert	25	25	78	18	9

No Start Up Kit Required

Optional 5-year Pump Warranty Available. See catalog for additional options

## Compressed Air Systems

Simplicity. It's What We Do.

[compressed-air-systems.com](http://compressed-air-systems.com) | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 4-2017

