

19 CFM Gas Compressor/Generator/Welder



**19 cfm @ 175 psi
5000 Watt Generator
240 Amp Welder**

Basic Compressor Features

- Heavy duty two stage solid cast iron pump
- Disk and spring valves
- Bearings on both ends of the crank shaft
- Centrifugal unloader
- Needle bearings, and inserts on rods
- Industrial grade gas engine
- ASME tested powder coated steel tank
- 2 groove B width motor pulley
- Access to compressor valves without compressor head removal
- Pilot valve continuous operation
- Fully enclosed belt guard
- Full saddle mounting feet instead of pegged mounting feet
- Alternator on driven engine

- 5500 Watt Generator
- 110/220 Volt Outlets
- 41 Amps @ 120 Volt
- 20 Amps @ 240 Volt
- Belt guard after cooler
- On-board battery mounted and wired (No wiring to the front of the truck needed)
- Automatic tank drain
- Vibration pads
- Freight pre-paid in the 48 states & southern Canada



Air cooled after cooler Elite unit



Model	HP	Mount	Tank	Drive Engine	Length	Width	Height	Weight
P140GEC8-GWE	13	Tank	8 Gallon Horizontal	Honda Electric start	46	26	30	550
P130GEH8-GWE	14	Tank	8 Gallon Horizontal	Honda Electric start	46	26	30	550
C130GEH34-GWE	13	Tank	30 Gallon Horizontal	Honda Electric start	46	26	42	550
C140GEC34-GWE	14	Tank	30 Gallon Horizontal	Kohler Electric start	46	26	42	550
BMC130GEH34-GWE	13	Base	30 Gallon Horizontal	Honda Electric start	46	26	42	550
BMC140GEC34-GWE	14	Base	30 Gallon Horizontal	Kohler Electric start	46	26	42	550

No start Up Kit Required

Optional 5-year Pump Warranty Available. See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 2-2017

