

# 10 HP Reciprocating



35 cfm @ 175 psi  
(3 phase)

34 cfm @ 175 psi  
(1 phase)

## Basic Compressor Features

- Heavy Duty two stage solid cast iron pump
- Disk and spring valves
- Bearings on both ends of the crank shaft
- Needle bearings, and inserts on rods
- Industrial grade electric motor
- ASME tested powder coated steel tank
- 2 groove B width motor pulley
- All UL electrical controls
- Access to compressor valves without compressor head removal
- Auto start stop
- Fully enclosed belt guard
- Heavy duty air filter
- Swedish steel valves
- Torrington needle bearings
- Centrifugal unloader
- Stainless steel flex air lines
- TEFC drive motor (3 phase only)

## Elite Compressor Features

- All basic features
- Belt guard after cooler
- Low oil monitor
- Automatic tank drain
- Vibration pads
- Tank discharge ball valve
- Freight pre-paid in the 48 states & southern Canada



Air cooled after cooler Elite unit

Model	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
B101V86	1	208-230	80 Gallon Vertical	36	24	74	42	N/A
B103V86	3	208-230-460	80 Gallon Vertical	36	24	74	28	14
B101H86	1	208-230	80 Gallon Horizontal	64	24	48	42	N/A
B103H86	3	208-230-460	80 Gallon Horizontal	64	24	48	28	14
B101V126	1	208-230	120 Gallon Vertical	42	34	84	42	N/A
B103V126	3	208-230-460	120 Gallon Vertical	42	34	84	28	14
B101H126	1	208-230	120 Gallon Horizontal	70	26	45	42	N/A
B103H126	3	208-230-460	120 Gallon Horizontal	70	26	45	28	14

Add E after part number to make Elite Model

**No Start Up Kit Required**

**Optional 5-year Pump Warranty Available.** See catalog for additional options.

## Compressed Air Systems

Simplicity. It's What We Do.

[compressed-air-systems.com](http://compressed-air-systems.com) | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 7-2016

