

5 HP Reciprocating



17.5 cfm @ 175 PSI

Basic Compressor Features

- Heavy duty two stage solid cast iron pump
- Disk and spring valves
- Bearings on both ends of the crank shaft
- Needle bearings, and inserts on rods
- Industrial grade electric motor
- ASME tested powder coated steel tank
- 2 groove B width motor pulley
- All UL electrical controls
- Access to compressor valves without compressor head removal
- Auto start stop
- Fully enclosed belt guard
- Heavy duty air filter
- Swedish steel valves
- Torrington needle bearings
- Magnetic starter mounted and wired
- Centrifugal unloader
- Stainless steel flex air lines
- TEFC drive motor (3 phase only)
- 2-piece tank top plate design

Elite Compressor Features

- All basic features
- Belt guard after cooler
- Low oil monitor
- Automatic tank drain
- Vibration pads
- Tank discharge ball valve
- Freight pre-paid in the 48 states & southern Canada



Model	Phase	Voltage	Tank	Length	Width	Height	Amp Draw 230 Volt	Amp Draw 480 Volt
B51V64	1	208-230	60 Gallon Vertical	32	24	74	24	N/A
B53V64	3	208-230-460	60 Gallon Vertical	32	24	74	16	8
B51V84	1	208-230	80 Gallon Vertical	32	26	78	24	N/A
B53V84	3	208-230-460	80 Gallon Vertical	32	26	78	16	8
B51H84	1	208-230	80 Gallon Horizontal	63	24	45	24	N/A
B53H84	3	208-230-460	80 Gallon Horizontal	63	24	45	16	8

Add E after model number to make Elite Model

No Start Up Kit Required

Optional 5-year Pump Warranty Available. See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 2-2018

