

# 50 HP Enclosed Rotary Screw



78 dBA

185 cfm @ 150 psi

215 cfm @ 125 psi

## Features

- Airend manufactured with German rotary screw components
- Air/oil cooler
- Automatic belt tensioning
- Easy to read and access gauges
- Easy to access oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Heavy duty air filter
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Solid steel sound enclosure
- Spin on separator
- TEFC drive motor (3 phase only)
- UL control components
- Vertical draft ventilation
- 220 PSI maximum working pressure

## CDR Compressor Features

- All basic features
- Air receiver
- ASME Powder coated air receiver
- Automatic tank drain
- Refrigerated air dryer
- SMART contact controls
- Stainless steel discharge lines
- Vibration isolation pads
- Free freight in the 48 states & southern Canada



| Model Number | Phase | Voltage     | Tank                | Package | Length | Width | Height | Amp Draw 230 Volt | Amp Draw 480 Volt |
|--------------|-------|-------------|---------------------|---------|--------|-------|--------|-------------------|-------------------|
| RS503ENC     | 3     | 208-230-460 | N/A                 | Basic   | 57     | 44    | 60     | 125/td>           | 63                |
| RS503ENC-CRD | 3     | 208-230-460 | 120 Gallon Vertical | CRD     | 57     | 44    | 60     | 125/td>           | 63                |

No Start Up Kit Required

Optional Lifetime Parts Warranty Available

See catalog for additional options

## Compressed Air Systems

Simplicity. It's What We Do.

[compressed-air-systems.com](http://compressed-air-systems.com) | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 7-2024

