

39 cfm Gas/Diesel Engine Driven Rotary Screw Compressor



39 cfm @ 150 psi

42 cfm @ 125 psi

Features

- Airend manufactured with German rotary screw components
- ASME Powder coated air receiver
- Drive engine on left side for safety
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Fully enclosed belt guard
- Full saddle mounting feet instead of pegged mounting feet
- Heavy duty air filter
- Industrial-duty drive engine
- Omega profile rotors
- Operating pressures from 100-190 psi available
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Spin on separator

Elite Stainless Features

- All Elite features
- First oil and filter change
- Stainless steel discharge lines
- Stainless steel 12 inch install line
- Tank discharge ball valve

Elite Package Features

- All basic features
- Air/oil cooler
- Battery mounted and wired
- SIMPLEX controls
- Tank discharge ball valve
- Vibration isolation pads
- Free freight in the 48 states & southern Canada



Model	HP	Mount	Tank	Drive Engine	Length	Width	Height
RS180GED30	17	Tank Mount	30 Gallon Horizontal	Kohler Diesel	48	36	48
RS180GEH30	18	Tank Mount	30 Gallon Horizontal	Honda	48	30	48
RS180GEC30	18	Tank Mount	30 Gallon Horizontal	Kohler	48	30	48

Add -E after model number to make Elite Model. Unit does not come standard with fuel tank.

No Start Up Kit Required

Optional 5-year Pump Warranty Available

See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 3-2019

