

24-35 cfm Gas/Diesel Engine Driven Rotary Screw Compressor/Generator



5500 Watt Generator

Features

- Air/oil cooler
- Airend manufactured with German rotary screw components
- ASME Powder coated air receiver
- Battery mounted and wired
- Compressor airend drive belt tensioning base
- Drive engine on left side for safety
- Easy to read and access gauges
- Easy to remove bolt on oil cooler for cleaning
- EPA approved exhaust system
- Extended oil drain with ball valve for easy service
- Factory filled with premium synthetic fluid
- Fully enclosed belt guard
- Full saddle mounting feet instead of pegged mounting feet
- Generator drive belt tensioning base
- Heavy duty air filter
- High temperature/high pressure hydraulic style air and oil lines
- Industrial-duty generator
- Industrial-grade drive engine
- 110 volt plugs
- 240 volt plug
- Omega profile rotors
- Operating pressures from 100-190 psi available
- OSHA belt guard
- Simplified operating controls, no complicated micro-processor
- Single control solenoid operation
- Spin on oil filter
- Spin on separator
- Solid saddle mounting feet
- Tank discharge ball valve
- Vibration isolation pads
- 2-piece tank and top plate design
- Free freight in the 48 states & southern Canada



Model Number	Engine	Tank Size	cfm @ 150 psi	Generator Max Watts	Length	Width	Height	Weight
RS130GEH30-GEN	Honda Gas	30 Gallon	20	5500	49	25	44	550
RS140GEC30-GEN	Kohler Gas	30 Gallon	20	5500	49	25	44	550
RS20GEH30-GEN	Honda Gas	30 Gallon	30	5500	51	28	44	550
RS250GEC30-GEN	Kohler Gas	30 Gallon	45	5500	51	28	46	550
RS260DEC30-GEN	Kohler Diesel	30 Gallon	45	5500	54	37	49	550

No Start Up Kit Required

Optional 5-year Pump Warranty Available

See catalog for additional options

Compressed Air Systems

Simplicity. It's What We Do.

compressed-air-systems.com | 1-800-531-9656 | Fax 972-352-6364

© Compressed Air Systems, LLC 3-2019

